



## Stabilizers Selection Chart - Compound

GS13	GS8	GS9
------	-----	-----

Draw Length	22"-25"	25"-27"	27"-29"	29"-31"	31"-33"
Poundage #					
20-30	28	28-30	28-30	30	30
	26	26-28	26-28-30	28-30	30
	-	28	28-30	28-30	30
30-40	28	28-30	28-30-32	30-32	30-32
	26	26-28	26-28-30	28-30-32	30-32
	-	28	28-30	28-30-32	30-32
40-50	28	28-30	28-30-32	30-32	30-32
	26	26-28	26-28-30	28-30-32	30-32
	-	28	28-30	28-30-32	30-32
50-60	28	28-30	28-30-32	30-32	30-32
	26	26-28-30	26-28-30	28-30-32	30-32
	-	28	28-30	28-30-32	30-32
60-70	28	28-30	28-30-32	28-30	30
	26	26-28-30	26-28-30	28-30-32	30-32
	-	28	28-30	28-30	30

### Selecting GILLO stabilizers for a Compound Bow Important Remarks

Table is suggesting models and length of Long Rod stabilizers suitable for Compound shooting, based on assumption that each long rod will have a GSX-UA Universal adapter on top, adding 1.5" in length and 35 g in weight

- Side Short Rod suggested :
  - 22 " to 27" draw length --> 10" Short Rods
  - 27" to 31" draw lengths ---> 10" or 12" Short rods
  - 31" and more in draw length --> 12" or 15" Short rods
- Also side rods here supposed to have a GSX-UA adapter on top

-The suggestions on the selection chart are based on stiffness and relative weight of each type of Long Rod, supposing that higher the poundage, more will be the mass weight archer will use on top of the Long Rod and stiffer it should be .  
They have to be considered as general suggestions only and submitted to real test on a given set-up.

#### General features of GILLO Stabilizers families:

- GS7----> 17 mm diameter, 1 mm wall, 30 ton carbon
- GS13 ---> 13 mm diameter, 3.5 mm wall, 40 ton carbon
- GS8 ----> 15 mm diameter, 3 mm wall, 40 Ton carbon
- GS9 ----> 13 mm diameter, 3.6 mm wall, 60 ton carbon
- GSX ----> Various parts matching all families of stabilizers
- GSJ ----> Side connectors for Short rods

Full technical specifications of GILLO Stabilizers are available from [www.gilloarchery.it](http://www.gilloarchery.it)